

Model PM220 series

OEM Pressure Transmitter
Ceramic pressure sensor
For Aggressive Media Applications

VOLLTEL
Sensing and Internet of Things

Features

- ❑ Measuring ranges from 200mbar to 50bar
- ❑ Gauge pressure
- ❑ Accuracy: $\pm 0.25\%$ FSO(Typ.)
- ❑ Pressure port PVDF/PP
- ❑ Ceramic pressure sensor
- ❑ Output 4...20mA, DC1...5V, DC0.5...4.5V, etc.



Application

- ❑ Mechanical and plant engineering
- ❑ Chemical industry
- ❑ Mechanical and plant engineering

Technical data

Pressure range

Nominal pressure [bar]	0.2	0.35	0.6	1	1.6	2.5	4	6	10	16	20	25	35	50		
Overpressure [bar]	0.4	0.5	1	1.5	3	5	7	10	15	30	30	35	40	60		

Performance

Accuracy*	0.25 %FS@25°C(Typ.) 0.5 %FS@25°C(Max.)	*Linearity (best straight line) + Hysteresis + Repeatability
Operating Temperature	0 to 60°C	
Compensated Temperature Range	0 to 60°C	
Vibration	20 g RMS(20 to 2000Hz)	
Shock	100 g(10ms)	
Cycles	10x10 ⁵	
Long Term Stability	0.3 %FS	

Electrical @25°C

Output signal / Supply	2-wire 4...20mA / V _S = 9... 30VDC
	3-wire 1...5VDC / V _S = 9... 30VDC
	3-wire 0.5...4.5VDC / V _S = 9... 30VDC
Insulation Resistance	100 MΩ@100VDC
EMC Test	IEC61000-6-2/IEC61000-6-3
Reverse polarity protection	No damage – no function

Physical Specifications

Pressure port material	PVDF/PP
Diaphragm	Ceramic (96% Al ₂ O ₃)
Oil Filling	NA
Protection	IP65
Weight	~200g


The listed specifications and dimensions are subject to change without prior notice

Model PM220 series

OEM Pressure Transmitter
Ceramic pressure sensor
For Aggressive Media Applications

VOLLTEL
Sensing and Internet of Things

Dimensions (All dimensions in mm)



Electrical connections

DIN175301-803-A	4...20mA 2-wire	1...5VDC 3-wire	0.5...4.5VDC 3-wire	Connector M12x1(4-pin)	4...20mA 2-wire	1...5VDC 3-wire	0.5...4.5VDC 3-wire
+Vcc	1	1	1	+Vcc	1	1	1
OUT	2	3	3	OUT	3	4	4
GND	NA	2	2	GND	NA	3	3

Ordering code

Model	Range	Type	Output	Pressure Port	Pressure port material	Electrical Connection
PM220	01 0.2bar	G Gauge	42 4...20mA	01 G1/4 male	M1 PVDF	E1 DIN175301-803A/IP65
	02 0.35bar	A Absolute	15 DC 1...5V	02 G1/2 male	M2 PP	E2 M12 connector/IP66
	03 0.6bar		05 DC 0...5V	03 1/4NPT male	M3 PTFE	E3 Cable outlet, 1.5m/IP66
	04 1bar		45 DC 0.5...4.5V	04 1/2NPT male		
	05 1.6bar		10 DC 0...10V	05 PT1/4 male		
	06 2.5bar		25 DC 0...2.5V	06 PT1/2 male		
	07 4bar		R4 RS485	07 M20x1.5 male		
	08 6bar		H1 HART	99 Custom		
	09 10bar					
	10 16bar					
	11 20bar					
	12 25bar					
	13 35bar					
	14 50bar					
	15 -0.1...+0.1bar					
	16 -0.2...+0.2bar					
	17 -1...0bar					
	18 -1...9bar					
	19 -1...16bar					
	20 -1...30bar					
	99 Custom					