

Model PM300W series

OEM Pressure Transmitter
Stainless steel flush diaphragm
For viscous and particle-laden media

VOLLTEL
Sensing and Internet of Things

Features

- Measuring ranges from 100mbar to 200bar
- Gauge pressure, Absolute pressure
- Accuracy: $\pm 0.5\%$ FSO(Typ.)
- Calibrated and temperature compensated
- Stainless steel flush diaphragm
- Output 4...20mA, DC1...5V, DC0.5...4.5V, RS485, etc.



Application

- Papermaking
- Process control systems
- Food and beverage
- Medical

Technical data

Performance

Accuracy*	$\pm 0.5\%$ FS@25°C(Typ.)	*Linearity (best straight line) + Hysteresis + Repeatability
Medium Temperature	-20 to 85°C, -20 to 125°C	
Compensated Temperature Range	-10 to 70°C	
Temp. coeff - Zero	± 0.75 [Typ.], ± 1.5 [Max.]	
Temp. coeff - Span	± 0.75 [Typ.], ± 1.5 [Max.]	
Vibration	20 g RMS(20 to 2000Hz)	
Shock	100 g(10ms)	
Cycles	10×10^5	
Long Term Stability	0.2 %FS[Typ.]	

Electrical @25°C

Output signal / Supply	2-wire	4...20mA / $V_s = 12...30$ VDC
	3-wire	1...5VDC / $V_s = 12...30$ VDC
	3-wire	0.5...4.5VDC / $V_s = 5$ VDC
	2-wire	4...20mA+HART / $V_s = 12...30$ VDC
	4-wire	RS485 Modbus RTU / $V_s = 12...30$ VDC
Insulation Resistance	100 M Ω @100VDC	
EMC Test	IEC61000-6-2/IEC61000-6-3	
Reverse polarity protection	No damage - no function	

Physical Specifications

Housing	304 stainless steel
Diaphragm	316L stainless steel
Sealing	NBR or Viton O-ring
Oil Filling	Silicone oil
Protection	IP65
Weight	~250g(without cable)

The listed specifications and dimensions are subject to change without prior notice

Model PM300W series

OEM Pressure Transmitter
Stainless steel flush diaphragm
For viscous and particle-laden media

VOLLTEL
Sensing and Internet of Things

Dimensions (All dimensions in mm)

Code E1 DIN175301-803A/DIN43650/IP65	Code E2 M12 connector/IP65	Code E3 Cable outlet, 1.5m/IP66
Code T2 With cooling element/(Temperature<125°)		

Electrical connections

DIN175301 -803-A	4...20mA 2-wire	1...5VDC 3-wire	0.5...4.5VDC 3-wire	RS485 4-wire
+Vcc	1	1	1	1
OUT	2	3	3	-
GND	-	2	2	2
RS485A	-	-	-	3
RS485B	-	-	-	-

Connector M12x1(4-pin)	4...20mA 2-wire	1...5VDC 3-wire	0.5...4.5VDC 3-wire	RS485 4-wire
+Vcc	1	1	1	1
OUT	3	4	4	-
GND	-	3	3	3
RS485A	-	-	-	2
RS485B	-	-	-	4

Model PM300W series

OEM Pressure Transmitter
Stainless steel flush diaphragm
For viscous and particle-laden media

VOLLTEL
Sensing and Internet of Things

Standard pressure range

Code	Pressure [bar]	Gauge	Absolute
01	0...0.1	✓	
02	0...0.16	✓	
03	0...0.25	✓	
04	0...0.4	✓	✓
05	0...0.5	✓	✓
06	0...1	✓	✓
07	0...1.6	✓	✓
08	0...2.5	✓	✓
09	0...4	✓	✓
10	0...6	✓	✓
11	0...10	✓	✓
12	0...16	✓	✓
13	0...25	✓	✓
14	0...40	✓	
15	0...60	✓	
16	0...100	✓	

Code	Pressure [bar]	Gauge	Absolute
17	-0.6...0	✓	✓
18	-0.4...0	✓	
19	-0.25...0	✓	
20	-0.1...0	✓	
21	-1...0	✓	
22	0...-1	✓	
23	-1...+1.5	✓	
24	-1...+3	✓	
25	-1...+9	✓	
26	-1...+15	✓	
27	-1...+16	✓	
28	-1...+24	✓	

Ordering code

Model	Range	Type	Output/Power supply	Pressure Port	Electrical Connection
PM300W	code	G Gauge	42 4...20mA/12...30VDC	01 G½ male	E1 DIN175301-803A/IP65
		A Absolute	15 DC 1...5V/12...30VDC	02 G1 male	E2 M12 connector/IP65
			05 DC 0...5V/12...30VDC	03 G1-½ male	E3 Cable outlet, 1.5m/IP66
			45 DC 0.5...4.5V/5VDC	04 M20x1.5 male	E4 Cable outlet, 1.5m/IP68
			10 DC 0...10V/15...30VDC	99 Custom	
			25 DC 0...2.5V/5VDC		
			R4 RS485 Modbus RTU/12... 30VDC		
			HR 4...20mA+HART /12... 30VDC		

Accuracy	Medium Temperature	Label
A1 0.25%FS	T1 -20 to 85°C	S Standard
A2 0.5%FS(Standard)	T2 -20 to 125°C	N Neutral packing
A3 1.0%FS	T3 -20 to 150°C	C Custom label